

*Der Partner in
Ihrer Nähe*



HEDEMANN
Gabelstapler

CESAB

CESAB product range

Counterbalanced, Warehouse Equipment,
Towing solutions



HEDEMANN
Gabelstapler

Hedemann GmbH
Oldenburger Straße 28
D-26639 Wiesmoor

Tel.: +49 (0) 49 44 / 14 50
Mail: kontakt@hedemann-stapler.de
Web: www.hedemann-stapler.de

Counterbalanced

4-wheel engine trucks torque converter

imd
isd



M
315 - 318
Stage V

	1.5 - 1.8 t
	6500 mm
	DIESEL/LPG

imd
isd



M
320 - 325
Stage V

	2.0 - 2.5 t
	7000 mm
	DIESEL/LPG

imd
isd



M
330 - 335
Stage V

	3.0 - 3.5 t
	7000 mm
	DIESEL/LPG

4-wheel engine trucks hydrostatic

imd
isd



M
315H - 318H
Stage V

	1.5 - 1.8 t
	6500 mm
	DIESEL/LPG

imd
isd



M
320H - 325H
Stage V

	2.0 - 2.5 t
	7000 mm
	DIESEL/LPG

imd
isd



M
330H - 335H
Stage V

	3.0 - 3.5 t
	7000 mm
	DIESEL/LPG

LEGEND

	Rated Lift / Load capacity		Maximum battery
	Rated towing capacity		Fuel type
	Maximum lifting height		Additional info

Der Partner in
Ihrer Nähe



HEDEMANN
Gabelstapler

3-wheel electric trucks

imd
isd



B
210 - 213 -
215

	1.0 - 1.25 - 1.5 t
	6500 mm
	24V / 875 Ah

imd
isd



B3
-15 -16
-16L -18 -18L
-20

	1.5 - 1.6 - 1.8 - 2.0 t
	7500 mm
	48V / 750 Ah

imd
isd
Li-ION



B3
-16-Li
-20-Li

	1.6 - 2.0 t
	7500 mm
	48V / 420Ah

4-wheel electric trucks

imd
isd



B4
-16
-16L -18L
-20 -20L

	1.6 - 1.8 - 2.0 t
	7500 mm
	48V / 750 Ah

imd
isd
Li-ION



B4
20L-Li

	2.0 t
	7500 mm
	48V / 420Ah

4-wheel electric trucks

imd
isd



B
620 - 625(L-HL)
630(L-HL) - 635

	2.0 - 2.5 - 3.0 - 3.5 t
	6500 mm
	80V / 775 Ah

imd



B
640 - 645
- 650

	4.0 - 4.5 - 5.0 t
	6500 mm
	80V / 930Ah

Heavy-duty electric trucks

isd



B
860 - 870
- 880(H)

	6.0 - 7.0 - 8.0 t
	7000 mm
	80V / 1240 Ah

Warehouse equipment

Hand pallet trucks



CE 200L - 230 - 300	 2.0 - 2.3 - 3.0 t
	 The 2.3 t model is also available with low forks, quicklift feature and handbrake. Low forks are standard on the 2.0 t model.



CE 200st	 2.0 t
	Stainless steel version.



H 210 - 210E	 1.0 t
	 800 mm
	 Available with manual and electric lift.

Powered pallet trucks

COMING SOON



P 013iB	 1.3 t
	 Li-Ion 24V/20Ah
	 Available with fast charger for 2½ hour charging time.



P 113	 1.3 t
	 24V / 63 Ah
	 Integrated batteries and charger.



P 214 - 216 - 218 - 220 - 225	 1.4 - 1.6 - 1.8 - 2.0 - 2.5 t
	 24V / 300 Ah
	 Optional operator platform available for P220.



P 216i	 1.6 t
	 Li-Ion 24V / 150 Ah
	 Available with internal or external charger.



P 320 - 322	 2.0 - 2.2 t
	 24V / 600 Ah
	 Available with a choice of travel speed (6,8,10 km/h).

Reach trucks



R 112 - 114 - 116	 1.2 - 1.4 - 1.6 t
	 8500 mm
	 48V / 620 Ah
	 Also available as a drive-in version with narrow overhead guard.

imd
Intelligent Machine Design



R 214 - 216	 1.4 - 1.6 t
	 10000 mm
	 48V / 620 Ah
	 Also available as a cold store version as well as drive-in version with narrow overhead guard.

imd
Intelligent Machine Design



R 314 - 316 - 318 - 320 - 325	 1.4 - 1.6 - 1.8 - 2.0 - 2.5 t
	 13000 mm
	 48V / 930 Ah
	 Also available as a cold store version, with or without heated cabin, as well as a drive-in version with narrow overhead guard.

Powered stacker trucks



S	KG	1.0 t
010i	↑	3600 mm
	B	Li-ion 24V / 60 Ah
i	Integrated battery and charger. Lift heights 2,9 and 3,6 m.	



S	KG	1.0 t
110 - 110S	↑	2000 mm
	B	24V / 63 Ah
i	Integrated batteries and charger. S110S: straddle support arm variant.	



S	KG	1.0 - 1.2 - 1.4 t
210 - 212 - 214	↑	4755 mm
	B	24V / 300 Ah
i	Optional operator platform available.	



S	KG	1.45 - 1.6 - 2.0 t
215 - 216 - 220	↑	6000 mm
	B	24V / 500 Ah
i	Available with a choice of chassis width.	



S	KG	0.8 t
208L	↑	1580 mm
	B	24V / 230 Ah
i	Can lift up to 2000 kg when lifting with the support arms only. Available with optional automatic height adjustment.	



S	KG	1.2 - 1.4 t
212L - 214L	↑	4755 mm
	B	24V / 300 Ah
i	Elevating support arms. Optional operator platform available.	



S	KG	1.45 - 1.6 - 2.0 t
215L - 216L - 220L	↑	6000 mm
	B	24V / 500 Ah
i	Elevating support arms.	



S	KG	1.0 t
220D	↑	2100 mm
	B	24V / 300 Ah
i	Double stacker, lifts 800 + 1200 kg lifting with forks + support arms or 2000 kg when lifting with the support arms only. Optional operator platform available.	



S	KG	1.2 t
212S	↑	4755 mm
	B	24V / 300 Ah
i	Straddle support arms. Optional operator platform also available.	



S	KG	1.4 t
214S	↑	5400 mm
	B	24V / 300 Ah
i	Straddle support arms variant.	



S	KG	1.2 - 1.4 - 1.6 - 2.0 t
312 - 314 - 316 - 320	↑	6000 mm
	B	24V / 500 Ah
i	Available with a choice of speeds up to 10km/h.	



S	KG	1.2 - 1.4 - 1.6 - 2.0 t
312L - 314L - 316L - 320L	↑	6000 mm
	B	24V / 500 Ah
i	Elevating support arms. Available with a choice of speed, up to 10km/h.	



S	KG	1.4 t
314S	↑	5400 mm
	B	24V / 500 Ah
i	Straddle support arms.	

Warehouse equipment

Low Level Order Pickers



125 – 125P

	2.5 t
	235 mm
	24V / 620 Ah
	The lifting platform version allows the driver to pick goods up to 2700 mm



112 – 112P

	1.2 t
	800 mm
	24V / 620 Ah
	The lifting platform version allows the driver to pick goods up to 2700 mm



120X – 118XP

	2.0 t / XP 1.8 t
	800 mm
	24V / 620 Ah
	The lifting platform version allows the driver to pick goods up to 2700 mm



110 – 110W

	1.0 t
	O110 - 1880 mm O110W - 1100 mm
	24V / 620 Ah
	Low step height 180 mm W version without barrier for handling bulky goods



112CB

	1.2 t
	4150 mm
	24V / 620 Ah
	2-in-1 solution, O112CB can be used for picking as well as stacking

Towing solutions

3-Wheel Tow Tractors

Tracto



TTE 40	↔	4.0 t
	KG	24V / 360 Ah
	i	For indoor towing application to feed assembly line

Tracto



TTE 71	↔	100 kg
	KG	48V 375Ah
	i	For indoor and occasional outdoor towing application. Possibility to have a closed cab.

4-Wheel Tow Tractors

Tracto



TE 80	↔	8.0 t
	KG	0.1 t
	KG	48V / 375 Ah
i	For indoor and outdoor towing application. 2nd seat possible. Closed cab available	

Tracto



TE 80IXB	↔	8.0 t
	KG	-
	KG	48V / 375 Ah
i	For indoor and outdoor towing application. 2nd seat possible. Closed cab available	

Tracto



TE 152	↔	15.0 t
	KG	0.2 t
	KG	48V / 625 Ah
i	For outdoor towing application. 2nd seat available. Cab with sliding or banging doors	

Tracto



TE 252	↔	25.0 t
	KG	0.2 t
	KG	80V / 620 Ah
i	For outdoor towing application. 2nd seat available. Cab with sliding or banging doors	

Tracto



TE 293	↔	29.0 t
	KG	0.2 t
	KG	80V / 620 Ah
i	For outdoor towing application. 2nd seat available. Cab with sliding or banging doors	

Tracto



TE 301	↔	30.0 t
	KG	0.1 t
	KG	80V / 620 Ah
i	For outdoor towing application. 2nd seat available. Bonnet cab with banging doors	

Tracto



TE 501	↔	50.0 t
	KG	0.2 t
	KG	80V / 930 Ah
i	For outdoor towing application. 2nd seat available. Cab with sliding or banging doors	

Platform Trucks

Tracto



PE 15.1	↔	10.0 t
	KG	1.5 t
	KG	48V / 500 Ah
i	For industrial transport. 2nd seat available. Platform can be customized with different equipment	

Tracto



PE 20.1	↔	10.0 t
	KG	2.0 t
	KG	48V / 480 Ah
i	For industrial transport. 2nd seat available. Platform can be customized with different equipment	



IMD

Intelligent Mast Design

IMD (Intelligent Mast Design) is a pioneering concept designed and engineered exclusively within the CESAB Group.

We believe that the mast is key to safe and productive materials handling. We use 3-D computer modelling, Finite Element Model analysis with a computerised simulation to find the best design solution for our masts.

Thanks to IMD, CESAB provides you with the industry leading levels of visibility and performance.

Among other advantages of the Intelligent Mast Design:

- High strength and rigidity
- Low maintenance
- Low energy usage
- Superior forward visibility
- Smooth operation
- More durability
- Productivity



By applying the IMD concept to the design of each individual truck, CESAB has created a range of forklifts that provide you outstanding performance.

The data in this document was determined based on our standard testing conditions. Operating performance may vary depending on the actual specification and condition of the truck as well as the condition of the operating area.
Availability and specifications are determined regionally and are subject to change without notice. Please consult your authorised CESAB dealership for further details.
Full Range Brochure EN v. 2025.02 – Copyright CESAB Material Handling Europe.